



Novaseeds

Smart Contract Security Audit

No. 202410182000

Oct 18th, 2024



SECURING BLOCKCHAIN ECOSYSTEM

WWW.BEOSIN.COM

Contents

1 Overview	5
1.1 Project Overview	5
1.2 Audit Overview	5
1.3 Audit Method	5
2 Findings	7
[Novaseeds-01] Improper design of receive function	8
[Novaseeds-02] The idoTokenA restriction deposit Issue	9
[Novaseeds-03] Code redundancy	10
3 Appendix	11
3.1 Vulnerability Assessment Metrics and Status in Smart Contracts	11
3.2 Audit Categories	14
3.3 Disclaimer	16
3.4 About Beosin	17

Summary of Audit Results

After auditing, 1 Low-risk and 2 info items were identified in the project. Specific audit details will be presented in the Findings section. Users should pay attention to the following aspects when interacting with this project:

Low

Fixed: 0 **Acknowledged: 1**

Info

Fixed : 0 **Acknowledged: 2**

- **Project Description**

Business overview

The TGPool and TGFactory contracts together form an Initial DEX Offering (IDO) native. The TGPool contract allows users to deposit native tokens via the DepositMNT function to participate in the IDO. Based on the deposited amount, token B is minted and distributed as follows: 79% to users, 1% to the creator, 19% to the liquidity pool, and 1% for native fees. After the IDO ends, users can claim their token B through the claim function, with the tokens released linearly based on the staking ratio. The contract uses a Merkle tree mechanism to ensure the correct token amount is claimed by the creator. Additionally, the owner can withdraw liquidity and manage the contract, including pausing or resuming operations. On the other hand, the TGFactory contract is responsible for creating and managing multiple TGPool instances, allowing authorized users to generate new pools through the createPool function and providing a query feature for pool addresses.

1 Overview

1.1 Project Overview

Project Name	Novaseeds
Project Language	Solidity
native	MNT Chain
Base code	https://github.com/novagroupd/contract-ido
Commit	ac15ea32547067afdf44f14d688aaf5256515ba6

1.2 Audit Overview

Audit work duration: Oct 17, 2024 – Oct 18, 2024

Audit team: Beosin Security Team

1.3 Audit Method

The audit methods are as follows:

1. Formal Verification

Formal verification is a technique that uses property-based approaches for testing and verification. Property specifications define a set of rules using Beosin's library of security expert rules. These rules call into the contracts under analysis and make various assertions about their behavior. The rules of the specification play a crucial role in the analysis. If the rule is violated, a concrete test case is provided to demonstrate the violation.

2. Manual Review

Using manual auditing methods, the code is read line by line to identify potential security issues. This ensures that the contract's execution logic aligns with the client's specifications and intentions, thereby safeguarding the accuracy of the contract's business logic.

The manual audit is divided into three groups to cover the entire auditing process:

The Basic Testing Group is primarily responsible for interpreting the project's code and conducting comprehensive functional testing.

The Simulated Attack Group is responsible for analyzing the audited project based on the collected historical audit vulnerability database and security incident attack models. They identify potential attack vectors and collaborate with the Basic Testing Group to conduct simulated attack tests.

The Expert Analysis Group is responsible for analyzing the overall project design, interactions with third parties, and security risks in the on-chain operational environment. They also conduct a review of the entire audit findings.

3. Static Analysis

Static analysis is a function of examining code during compilation or static analysis to detect issues. Beosin-VaaS can detect more than 100 common smart contract vulnerabilities through static analysis, such as reentrancy and block parameter dependency. It allows early and efficient discovery of problems to improve code quality and security.

2 Findings

Index	Risk description	Severity level	Status
Novaseeds-01	Improper design of receive function	Low	Acknowledged
Novaseeds-02	The idoTokenA restriction deposit Issue	Info	Acknowledged
Novaseeds-03	Code redundancy	Info	Acknowledged

Finding Details:

[Novaseeds-01] Improper design of receive function

Severity Level	Low
Lines	TGPool.sol#L411-143
Type	Business Security
Description	Since this project only supports deposits in the native token, the contract includes a receive method to accept the native token. However, this method does not perform the corresponding staking operation. If users directly transfer the native token to participate in staking, it will result in a staking failure, and those funds will remain in the contract.
Recommendation	It is recommended to implement the staking function in the <code>receive</code> function.
Status	Acknowledged.

[Novaseeds-02] The idoTokenA restriction deposit Issue

Severity Level	Info
Lines	TGPool.sol#L185
Type	Business Security
Description	The contract requires <code>idoTokenA</code> to be a zero address, but it also asks the creator to input that address during creation. If the creator inputs an <code>idoTokenA</code> that is not a zero address, it will prevent users from making deposits.
Recommendation	It is recommended that the contract does not require setting the value of <code>idoTokenA</code> during creation.
Status	Acknowledged.

[Novaseeds-03] Code redundancy

Severity Level	Info
Lines	TGPool.sol#L217-219
Type	Coding Conventions
Description	In the TGPool.sol contract, lines L217-219 incorrectly calculate <code>rewardPerSecond</code> without dividing by 1000. Additionally, <code>rewardPerSecond</code> is recalculated later, making this portion of the code redundant.
Recommendation	It is recommended to remove redundant code.
Status	Acknowledged.

3 Appendix

3.1 Vulnerability Assessment Metrics and Status in Smart Contracts

3.1.1 Metrics

In order to objectively assess the severity level of vulnerabilities in blockchain systems, this report provides detailed assessment metrics for security vulnerabilities in smart contracts with reference to CVSS 3.1 (Common Vulnerability Scoring System Ver 3.1).

According to the severity level of vulnerability, the vulnerabilities are classified into four levels: "critical", "high", "medium" and "low". It mainly relies on the degree of impact and likelihood of exploitation of the vulnerability, supplemented by other comprehensive factors to determine of the severity level.

Impact \ Likelihood	Severe	High	Medium	Low
Probable	Critical	High	Medium	Low
Possible	High	Medium	Medium	Low
Unlikely	Medium	Medium	Low	Info
Rare	Low	Low	Info	Info

3.1.2 Degree of impact

- **Critical**

Critical impact generally refers to the vulnerability can have a serious impact on the confidentiality, integrity, availability of smart contracts or their economic model, which can cause substantial economic losses to the contract business system, large-scale data disruption, loss of authority management, failure of key functions, loss of credibility, or indirectly affect the operation of other smart contracts associated with it and cause substantial losses, as well as other severe and mostly irreversible harm.

- **High**

High impact generally refers to the vulnerability can have a relatively serious impact on the confidentiality, integrity, availability of the smart contract or its economic model, which can cause a greater economic loss, local functional unavailability, loss of credibility and other impact to the contract business system.

- **Medium**

Medium impact generally refers to the vulnerability can have a relatively minor impact on the confidentiality, integrity, availability of the smart contract or its economic model, which can cause a small amount of economic loss to the contract business system, individual business unavailability and other impact.

- **Low**

Low impact generally refers to the vulnerability can have a minor impact on the smart contract, which can pose certain security threat to the contract business system and needs to be improved.

3.1.3 Likelihood of Exploitation

- **Probable**

Probable likelihood generally means that the cost required to exploit the vulnerability is low, with no special exploitation threshold, and the vulnerability can be triggered consistently.

- **Possible**

Possible likelihood generally means that exploiting such vulnerability requires a certain cost, or there are certain conditions for exploitation, and the vulnerability is not easily and consistently triggered.

- **Unlikely**

Unlikely likelihood generally means that the vulnerability requires a high cost, or the exploitation conditions are very demanding and the vulnerability is highly difficult to trigger.

- **Rare**

Rare likelihood generally means that the vulnerability requires an extremely high cost or the conditions for exploitation are extremely difficult to achieve.

3.1.4 Fix Results Status

Status	Description
Fixed	The project party fully fixes a vulnerability.
Partially Fixed	The project party did not fully fix the issue, but only mitigated the issue.
Acknowledged	The project party confirms and chooses to ignore the issue.

3.2 Audit Categories

No.	Categories	Subitems
1	Coding Conventions	Compiler Version Security
		Deprecated Items
		Redundant Code
		require/assert Usage
		Gas Consumption
2	General Vulnerability	Integer Overflow/Underflow
		Reentrancy
		Pseudo-random Number Generator (PRNG)
		Transaction-Ordering Dependence
		DoS (Denial of Service)
		Function Call Permissions
		call/delegatecall Security
		Returned Value Security
		tx.origin Usage
		Replay Attack
		Overriding Variables
Third-party Protocol Interface Consistency		
3	Business Security	Business Logics
		Business Implementations
		Manipulable Token Price
		Centralized Asset Control
		Asset Tradability
		Arbitrage Attack

Beosin classified the security issues of smart contracts into three categories: Coding Conventions, General Vulnerability, Business Security. Their specific definitions are as follows:

- **Coding Conventions**

Audit whether smart contracts follow recommended language security coding practices. For example, smart contracts developed in Solidity language should fix the compiler version and do not use deprecated keywords.

- **General Vulnerability**

General Vulnerability include some common vulnerabilities that may appear in smart contract projects. These vulnerabilities are mainly related to the characteristics of the smart contract itself, such as integer overflow/underflow and denial of service attacks.

- **Business Security**

Business security is mainly related to some issues related to the business realized by each project, and has a relatively strong pertinence. For example, whether the lock-up plan in the code match the white paper, or the flash loan attack caused by the incorrect setting of the price acquisition oracle.

* Note that the project may suffer stake losses due to the integrated third-party protocol. This is not something Beosin can control. Business security requires the participation of the project party. The project party and users need to stay vigilant at all times.

3.3 Disclaimer

The Audit Report issued by Beosin is related to the services agreed in the relevant service agreement. The Project Party or the Served Party (hereinafter referred to as the "Served Party") can only be used within the conditions and scope agreed in the service agreement. Other third parties shall not transmit, disclose, quote, rely on or tamper with the Audit Report issued for any purpose.

The Audit Report issued by Beosin is made solely for the code, and any description, expression or wording contained therein shall not be interpreted as affirmation or confirmation of the project, nor shall any warranty or guarantee be given as to the absolute flawlessness of the code analyzed, the code team, the business model or legal compliance.

The Audit Report issued by Beosin is only based on the code provided by the Served Party and the technology currently available to Beosin. However, due to the technical limitations of any organization, and in the event that the code provided by the Served Party is missing information, tampered with, deleted, hidden or subsequently altered, the audit report may still fail to fully enumerate all the risks.

The Audit Report issued by Beosin in no way provides investment advice on any project, nor should it be utilized as investment suggestions of any type. This report represents an extensive evaluation process designed to help our customers improve code quality while mitigating the high risks in blockchain.

3.4 About Beosin

Beosin is the first institution in the world specializing in the construction of blockchain security ecosystem. The core team members are all professors, postdocs, PhDs, and Internet elites from world-renowned academic institutions. Beosin has more than 20 years of research in formal verification technology, trusted computing, mobile security and kernel security, with overseas experience in studying and collaborating in project research at well-known universities. Through the security audit and defense deployment of more than 2,000 smart contracts, over 50 public blockchains and wallets, and nearly 100 exchanges worldwide, Beosin has accumulated rich experience in security attack and defense of the blockchain field, and has developed several security products specifically for blockchain.



BEOSIN
Web3 Security & Compliance



Official Website

<https://www.beosin.com>



Telegram

<https://t.me/beosin>



Twitter

https://twitter.com/Beosin_com



Email

service@beosin.com

